

Archives of Biochemical Engineering

Review Article

Prevalence and Risk Factors of low bioreactor yield in pilot-scale bioreactors

Yoshida H^{1*}, Kato T² and Nakamura K³

¹Department of Biochemical Engineering, Euphrates Institute of Bioprocess Technology, Japan

²Department of Biochemical Engineering, Yamuna Research Center for Biochemical Engineering, Japan

³Department of Bioprocess Technology, Amur Academy of Biochemical Engineering, South Korea

*Address for Correspondence: Hiroshi Yoshida, Department of Biochemical Engineering, Euphrates Institute of Bioprocess Technology, Japan; E-mail: hiroshi.yoshida@euphrates.edu

Received: 27 September 2025; Accepted: 31 December 2025; Published: 26 March 2026.

Citation of this article: Yoshida H, Kato T, Nakamura K (2026) Prevalence and Risk Factors of low bioreactor yield in pilot-scale bioreactors. Arch Biochem Eng, 1(1): 01-06. DOI: [10.5281/zenodo.22812480](https://doi.org/10.5281/zenodo.22812480)

Copyright: © 2026 Hiroshi Yoshida, et al. This is an open access article distributed under the [Creative Commons Attribution License](#), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Abstract

Background: Pilot-scale fermentation is the stage at which processes that perform reliably on the bench most often fall short of their expected yield, and the engineering literature attributes this shortfall to a recurring set of scale-dependent risk factors rather than a single defect [3,1].

Objective: This review synthesizes the prevalence and mechanisms of the principal risk factors reported for low yield in pilot-scale bioreactors and summarizes the mitigation strategies most consistently supported by the scale-up and scale-down literature.

Methods: We synthesized peer-reviewed bioprocess engineering reviews, scale-down simulation studies, and mechanistic mass-transfer and mixing studies addressing stirred-tank bioreactors in the approximately 20-2000 L pilot-scale range.

Findings: Oxygen transfer limitation and mixing-time-driven substrate and pH gradients are the most frequently documented and mechanistically best-characterized risk factors [3,12,20], with hydrodynamic stress, contamination, foaming, and instrumentation drift as recurring secondary contributors [17,25,26].

Conclusions: Pilot-scale yield loss is best understood as a heterogeneity problem produced by the physical mismatch inherent in scale-up rather than a single broken parameter, and scale-down simulation combined with gradient-aware process design most consistently narrows the gap between bench and pilot performance [29,34].

Keywords: bioreactor scale-up; pilot-scale fermentation; oxygen transfer; mixing time; yield loss

1. Introduction

Pilot-scale fermentation is the step at which a process that behaved predictably on the bench is first asked to perform under the mixing, aeration, and control constraints of a vessel large enough to approximate production geometry. It is also, empirically, the step at which yield most often falls short of expectation. A process that reaches a target titer reliably at 1-5 L frequently loses 10-40% of its expected yield when transferred to a 50-2000 L pilot vessel, even when temperature, pH and dissolved-oxygen setpoints are nominally unchanged, and the shortfall is rarely traced to a single cause [1,2]. The engineering literature has spent more than four decades documenting why this happens, and a consistent picture has emerged: yield loss at pilot scale is driven less by any one dominant defect than by a recurring, overlapping set of risk factors rooted in the physical consequence of making a vessel bigger while keeping its biology the same [3,4].

The central difficulty is that geometric and dynamic similarity cannot be preserved simultaneously on scale-up. Power input per unit volume, impeller tip speed, mixing time, and volumetric mass-transfer coefficient (kLa) all scale differently with vessel diameter, so a pilot reactor matched to the bench on one criterion is necessarily mismatched on the others [5,6]. The consequence is that cells circulating through a large vessel repeatedly transit zones of differing substrate, oxygen, pH, and shear that a small, well-mixed bench reactor never generates, and this heterogeneity, not any single instrument failure, is the mechanistic thread running through most reported cases of pilot-scale yield shortfall [7,8]. This review synthesizes the prevalence and mechanisms of the principal risk factors reported for low yield in pilot-scale bioreactors, drawing on scale-up methodology reviews, scale-down simulation studies, and process-troubleshooting literature spanning microbial and mammalian cell systems, and presents a synthesis of where these risks concentrate and how they are commonly mitigated.

2. Methods

This is a narrative synthesis of the peer-reviewed bioprocess engineering and biotechnology literature addressing scale-up performance loss, scale-down simulation, and risk factors for reduced yield in stirred-tank bioreactors operated in the pilot-scale range (approximately 20 L to 2000 L working volume). Sources were drawn from established reviews of bioreactor scale-up methodology [3,1,2,4,9,10], primary experimental studies using scale-down two- and multi-compartment reactors to reproduce large-scale gradients under controlled bench conditions [11,12,13,14], and mechanistic studies of mass transfer, mixing, and shear in stirred vessels [6,5,15,16,17,18]. Studies were included where they reported a quantifiable performance loss (titer, biomass yield, product quality, or productivity) attributable to a scale-dependent physical or operational factor, or where they characterized the magnitude of a scale-dependent gradient (oxygen, substrate, pH, shear) relevant to yield. Papers addressing purely upstream cell-line or strain engineering without a scale-dependent component were excluded, as were single-vessel case reports without a stated mechanism. Risk factors extracted from the included literature were grouped into recurring categories by mechanism (mass-transfer limitation, mixing-driven concentration gradients, hydrodynamic/shear stress, contamination and aseptic-boundary failure, foam-related loss, and control-loop or instrumentation error) and cross-referenced against reported scale-up case studies to characterize their relative prevalence and typical magnitude of yield impact, summarized quantitatively in the figures and tables below. Because reported magnitudes vary with organism, vessel geometry, and operating regime, the figures present representative ranges drawn from the cited scale-down and scale-up literature rather than a single controlled dataset, and should be read as an illustrative synthesis of the reviewed studies rather than a meta-analytic pooled estimate.

3. Results

Oxygen transfer limitation dominates the reported risk-factor literature

Oxygen transfer limitation is the single most frequently cited mechanism for pilot-scale yield loss in aerobic microbial fermentation. The volumetric mass-transfer coefficient, kLa , is governed by power input per unit volume and superficial gas velocity, both of which decline substantially when a process is scaled up under practical power and gas-supply constraints, so a vessel that never becomes oxygen-limited at bench scale can become severely so at pilot and production scale [3,19]. Islam and colleagues, matching kLa across microwell, shake-flask, and stirred bioreactor scales for recombinant *Escherichia coli*, showed that oxygen transfer capacity, rather than nominal working volume, was the parameter that had to be preserved for growth and recombinant protein yield to translate reliably between scales, and that reactors matched only on agitation rate or aeration rate alone produced systematically lower yields at the larger scale [20]. Van't Riet's classical review established the empirical correlations linking kLa to power input and gas velocity that remain the basis for scale-up kLa prediction, and the same correlations show why kLa falls disproportionately as vessel diameter increases under constant specific power input, since achievable superficial gas velocity is constrained by flooding and foaming limits in large vessels [6]. Humphrey's widely cited retrospective on shake-flask-to-fermenter transitions similarly attributes a large share of unexplained scale-up yield loss to oxygen transfer mismatch that was not apparent until the process reached a vessel large enough for mass transfer, rather than kinetics, to become rate-limiting [21].

Mixing time and concentration gradients produce metabolic heterogeneity

Beyond bulk oxygen supply, the time required to homogenize a feed or base addition across a large vessel scales unfavorably with size, and this mixing time, typically well under a second in a bench reactor, can

extend to tens of seconds in a pilot or production vessel [5,16]. Cells circulating past the feed or base addition point therefore experience transient spikes in substrate or pH before dilution, and cells elsewhere in the vessel simultaneously experience relative substrate or oxygen depletion, a spatial heterogeneity with no bench-scale counterpart [8,7]. Bylund and colleagues, using a scale-down two-compartment system to reproduce the substrate gradients measured in a large-scale *Escherichia coli* fermentation, showed directly that imposing such gradients on an otherwise identical culture lowered cell yield on substrate and increased by-product (acetate) formation relative to a well-mixed control, establishing a causal, not merely correlative, link between mixing-driven gradients and reduced yield [12]. Xu and colleagues extended this observation, showing that overflow metabolism and acetate excretion in glucose-limited *Escherichia coli* cultures intensified specifically under the intermittent substrate excess produced by incomplete mixing, consuming carbon that would otherwise support biomass or product formation [22]. George and colleagues' original scale-down two-compartment design, and Neubauer and colleagues' extension of it to fed-batch cultivation, both confirmed that substrate oscillation on a timescale matched to large-scale mixing times reduces growth yield even when total substrate delivered is unchanged, isolating gradient exposure itself, rather than total nutrient supply, as the operative risk factor [11,23]. Kass and colleagues reported comparable process inhomogeneity effects with rapid by-product turnover in *Corynebacterium glutamicum* cultivation, indicating that the mechanism generalizes across production organisms rather than being specific to *E. coli* [14].




Figure 1: Representative decline in volumetric oxygen transfer coefficient (kLa) from bench to pilot to production scale under practical power-input and gas-supply constraints, synthesized from scale-up methodology and kLa-matching studies [3,6,20].




Figure 2: Representative mixing time at bench, pilot, and production scale, illustrating the widening exposure window during which cells encounter substrate, oxygen, or pH gradients as vessel size increases [5,16,8].

pH excursions, hydrodynamic stress, and contamination

Localized pH excursions near base or acid addition points compound the substrate-gradient problem in large vessels. Amanullah and colleagues used a scale-down model to reproduce the spatial pH variation measured in a full-scale bioreactor and found that exposure to transient pH excursions materially altered fermentation performance in ways a well-controlled bench run would not predict [13], and Langheinrich and Nienow reported that alkali addition in large-scale, free-suspension animal cell bioreactors produces localized pH and osmolality excursions capable of directly injuring shear-sensitive mammalian cells at the point of addition even while the bulk pH probe reads within specification [24]. Hydrodynamic stress is a related and scale-amplified risk: Chisti's reviews of shear damage in sparged and stirred bioreactors document that impeller tip speed and the

energy dissipation rate near the impeller both tend to rise on scale-up under fixed volumetric power input, so cells or fragile product complexes that tolerate bench-scale agitation without measurable damage can suffer reduced viability, altered morphology, or lower specific productivity once vessel size and impeller geometry change [17,18]. Contamination and aseptic-boundary failure remain a distinct but frequently co-occurring risk category at pilot scale, where the number of sterile connections, sampling ports, and sensor penetrations is far greater than at bench scale, and Sandle's review of contamination control in bioreactor operations identifies port and probe integrity, steam-in-place validation, and monitoring frequency as the principal points of failure that convert an otherwise well-run pilot batch into a lost one [25].

Foaming and instrumentation drift as secondary but recurring factors

Foam formation, driven by protein and surfactant accumulation and amplified by the higher gas throughput needed to sustain kLa at larger scale, is reported repeatedly as both a direct yield-reducing factor, through loss of culture volume, antifoam-related interfacial stress, and blocked exhaust filters, and an indirect one, because aggressive foam control (mechanical breakers, elevated antifoam dosing) itself perturbs oxygen transfer and, in shear-sensitive cultures, cell integrity [26,27]. Instrumentation and control-loop performance form a final, less mechanistically distinct but operationally significant category: dissolved-oxygen and pH probes drift and respond more slowly at pilot scale relative to the volumes and gradients they must track, and several of the scale-down and troubleshooting reviews synthesized here note that a substantial fraction of yield shortfalls initially attributed to biological variability were, on closer investigation, control-loop or calibration artifacts rather than genuine scale-dependent physiology [28,29,9]. Table 1 summarizes these risk-factor categories, their principal mechanism, and the mitigation approaches most

consistently reported across the synthesized literature, and Table 2 compares representative mixing-time and kLa ranges reported across bench, pilot, and production scales, illustrating the magnitude of the physical mismatch underlying most of the categories above.

Table 1: Principal risk-factor categories for low yield in pilot-scale bioreactors, their mechanism, and the mitigation most consistently reported in the synthesized literature.		
Risk factor	Mechanism	Typical mitigation
Oxygen transfer limitation	kLa falls with vessel size under fixed specific power input	kLa-matched scale-up; sparger/impeller redesign [3,20]
Substrate/pH gradients	Long mixing time creates transient feed and base excursions	Scale-down simulation; multi-point feed/base addition [12,13]
Hydrodynamic/shear stress	Local energy dissipation rises near impeller on scale-up	Impeller selection; tip-speed limits [17,18]
Contamination/aseptic failure	More ports, probes and connections than bench scale	SIP/CIP validation; probe integrity checks [25]
Foaming	Higher gas throughput and protein accumulation	Mechanical breakers; optimized antifoam dosing [26,27]
Instrumentation/control drift	Slower probe response relative to vessel gradients	Calibration schedule; redundant sensing [29,28]

Table 2: Representative mixing-time and kLa ranges reported across bench, pilot, and production scale stirred-tank bioreactors [6,5,19].			
Scale	Working volume	Mixing time	kLa
Bench	1-5 L	< 5 s	100-300 h ⁻¹
Pilot	50-2000 L	10-60 s	30-100 h ⁻¹
Production	10,000-100,000 L	60-180 s	10-50 h ⁻¹

4. Discussion

The pattern across this literature is that pilot-scale yield loss is best understood as a heterogeneity problem rather than a single-fault problem. Almost every category identified here, oxygen transfer, substrate and pH gradients, hydrodynamic stress, and even foam and instrumentation issues, traces back to the same root cause: a larger vessel cannot preserve the near-uniform

micro-environment that a small, well-mixed bench reactor provides by default, and cells respond to the resulting spatial and temporal fluctuations with altered metabolism, reduced growth or product yield, or increased by-product formation [30,31]. Delvigne and colleagues demonstrated this directly at single-cell resolution, showing that reduced mixing efficiency in a stirred bioreactor measurably altered stress-promoter reporter activity in a recombinant Escherichia coli population, confirming that the yield consequences documented at the population level originate in genuinely heterogeneous single-cell exposure rather than a uniform, vessel-wide shift in conditions [32]. This reframing matters practically because it argues against troubleshooting pilot-scale yield loss as a search for a single broken parameter. Noorman's industrial perspective and Formenti and colleagues' survey of persistent industrial fermentation challenges both make the same point from an operations standpoint: production-scale performance gaps are rarely resolved by tightening a single setpoint, and are more often addressed by combining scale-down simulation of the actual large-scale gradients with regime analysis that identifies which gradient (oxygen, substrate, or pH) is rate-limiting for the specific organism and process at hand [29,28,33].

Scale-down simulation, in which a bench-scale system deliberately reproduces the substrate, oxygen, or pH oscillations measured or predicted for the large vessel, has become the most consistently validated tool for anticipating these losses before a costly pilot run rather than diagnosing them after the fact [34,11]. Its value is that it converts an otherwise qualitative concern, "will this process scale," into a quantifiable, testable yield comparison at bench scale, and the cited studies collectively show that gradient-exposed cultures reproduce the yield and by-product signatures actually observed at pilot and production scale with reasonable fidelity across both microbial and, to a more limited extent, mammalian systems [12,14,35]. The practical

implication for a laboratory moving a process into pilot-scale bioreactors for the first time is that mixing time and kLa should be characterized and, where feasible, matched or scale-down-simulated before the transfer, that pH and base-addition strategy should be re-evaluated for localized excursion risk rather than assumed adequate because bulk setpoints are unchanged, and that aseptic-boundary integrity and foam-control strategy should be validated as process variables in their own right rather than treated as fixed infrastructure [25,26,24]. None of these measures eliminates the physical mismatch inherent in scale-up, but the literature synthesized here indicates that anticipating which risk factor is likely to dominate for a given organism and vessel geometry, rather than treating yield loss as an undifferentiated scale-up penalty, is what most consistently narrows the gap between bench and pilot performance.

5. Conclusion

Low yield at pilot scale is rarely attributable to a single cause; it is the composite consequence of oxygen transfer limitation, mixing-driven substrate and pH heterogeneity, hydrodynamic stress, contamination risk, foaming, and instrumentation drift, all of which are amplified relative to the bench precisely because geometric and dynamic similarity cannot be preserved together on scale-up [3,5]. Across the scale-down and scale-up literature synthesized here, oxygen transfer and mixing-time mismatch emerge as the most frequently documented and best mechanistically characterized risk factors, with substantial supporting evidence that reproducing large-scale gradients at bench scale predicts the resulting yield loss with useful accuracy [20,12]. Recognizing pilot-scale yield loss as predominantly a heterogeneity problem, rather than searching for a single defective parameter, is the perspective most consistently supported by the reviewed evidence, and it points toward scale-down simulation, gradient-aware pH and feed strategy, and explicit validation of aseptic and foam-control performance as the interventions most likely

to close the gap between bench-scale promise and pilot-scale delivery.

6. References

1. Junker, B.H. (2004) Scale-up methodologies for *Escherichia coli* and yeast fermentation processes. *Journal of Bioscience and Bioengineering*, 97(6): 347-364.
2. Schmidt, F.R. (2005) Optimization and scale up of industrial fermentation processes. *Applied Microbiology and Biotechnology*, 68(4): 425-435.
3. Garcia-Ochoa, F., Gomez, E. (2009) Bioreactor scale-up and oxygen transfer rate in microbial processes: an overview. *Biotechnology Advances*, 27(2): 153-176.
4. Marques, M.P.C., Cabral, J.M.S., Fernandes, P. (2010) Bioprocess scale-up: quest for the parameters to be used as criterion to move from microreactors to lab-scale. *Journal of Chemical Technology and Biotechnology*, 85(9): 1184-1198.
5. Nienow, A.W. (1998) Hydrodynamics of stirred bioreactors. *Applied Mechanics Reviews*, 51(1): 3-32.
6. van't Riet, K. (1979) Review of measuring methods and results in nonviscous gas-liquid mass transfer in stirred vessels. *Industrial and Engineering Chemistry Process Design and Development*, 18(3): 357-364.
7. Lara, A.R., Galindo, E., Ramirez, O.T., Palomares, L.A. (2006) Living with heterogeneities in bioreactors: understanding the effects of environmental gradients on cells. *Molecular Biotechnology*, 34(3): 355-381.
8. Enfors, S.O., Jahic, M., Rozkov, A., Xu, B., Hecker, M., Jurgen, B., et al. (2001) Physiological responses to mixing in large scale bioreactors. *Journal of Biotechnology*, 85(2): 175-185.
9. Takors, R. (2012) Scale-up of microbial processes: impacts, tools and open questions. *Journal of Biotechnology*, 160(1-2): 3-9.
10. Crater, J.S., Lievense, J.C. (2018) Scale-up of industrial microbial processes. *FEMS Microbiology Letters*, 365(13):

- fny138.
11. George, S., Larsson, G., Enfors, S.O. (1993) A scale-down two-compartment reactor with controlled substrate oscillations: metabolic response of *Saccharomyces cerevisiae*. *Bioprocess Engineering*, 9(6): 249-257.
 12. Bylund, F., Collet, E., Enfors, S.O., Larsson, G. (1998) Substrate gradient formation in the large-scale bioreactor lowers cell yield and increases by-product formation. *Bioprocess Engineering*, 18(3): 171-180.
 13. Amanullah, A., McFarlane, C.M., Emery, A.N., Nienow, A.W. (2001) Scale-down model to simulate spatial pH variations in large-scale bioreactors. *Biotechnology and Bioengineering*, 73(5): 390-399.
 14. Kass, F., Junne, S., Neubauer, P., Wiechert, W., Oldiges, M. (2014) Process inhomogeneity leads to rapid side product turnover in cultivation of *Corynebacterium glutamicum*. *Microbial Cell Factories*, 13: 6.
 15. Oosterhuis, N.M.G., Kossen, N.W.F. (1984) Dissolved oxygen concentration profiles in a production-scale bioreactor. *Biotechnology and Bioengineering*, 26(5): 546-550.
 16. Manfredini, R., Cavallera, V., Marini, L., Donati, G. (1983) Mixing and oxygen transfer in conventional stirred fermenters. *Biotechnology and Bioengineering*, 25(12): 3115-3131.
 17. Chisti, Y. (2000) Animal-cell damage in sparged bioreactors. *Trends in Biotechnology*, 18(10): 420-432.
 18. Chisti, Y. (2001) Hydrodynamic damage to animal cells. *Critical Reviews in Biotechnology*, 21(2): 67-110.
 19. Garcia-Ochoa, F., Gomez, E., Santos, V.E., Merchuk, J.C. (2010) Oxygen uptake rate in microbial processes: an overview. *Biochemical Engineering Journal*, 49(3): 289-307.
 20. Islam, R.S., Tisi, D., Levy, M.S., Lye, G.J. (2008) Scale-up of *Escherichia coli* growth and recombinant protein expression conditions from microwell to laboratory and pilot scale based on matched kLa. *Biotechnology and Bioengineering*, 99(5): 1128-1139.
 21. Humphrey, A. (1998) Shake flask to fermentor: what have we learned? *Biotechnology Progress*, 14(1): 3-7.
 22. Xu, B., Jahic, M., Enfors, S.O. (1999) Glucose overflow metabolism and mixing-limited fermentation of *Escherichia coli*. *Biotechnology and Bioengineering*, 63(4): 442-449.
 23. Neubauer, P., Haggstrom, L., Enfors, S.O. (1995) Influence of substrate oscillations on acetate formation and growth yield in *Escherichia coli* glucose limited fed-batch cultivations. *Biotechnology and Bioengineering*, 47(2): 139-146.
 24. Langheinrich, C., Nienow, A.W. (1999) Control of pH in large-scale, free suspension animal cell bioreactors: alkali addition and pH excursions. *Biotechnology and Bioengineering*, 66(3): 171-179.
 25. Sandle, T. (2014) Contamination control and bioreactor monitoring: assessing risk factors in cell culture and microbial fermentation processes. *Journal of Validation Technology*, 20(3): 1-10.
 26. Junker, B.H. (2007) Foam and its mitigation in fermentation systems. *Biotechnology Progress*, 23(4): 767-784.
 27. Etoc, A., Delvigne, F., Lecomte, J.P., Thonart, P. (2006) Foam control in fermentation bioprocess: from simple aeration tests to bioreactor. *Applied Biochemistry and Biotechnology*, 130(1-3): 392-404.
 28. Formenti, L.R., Norregaard, A., Bolic, A., Hernandez, D.Q., Hagemann, T., Heins, A.L., et al. (2014) Challenges in industrial fermentation technology research. *Biotechnology Journal*, 9(6): 727-738.
 29. Noorman, H. (2011) An industrial perspective on bioreactor scale-down: what we can learn from combined large-scale bioprocess and model fluid studies. *Biotechnology Journal*, 6(8): 934-943.
 30. Delvigne, F., Goffin, P. (2014) Microbial heterogeneity affects

bioprocess robustness: dynamic single-cell analysis contributes to understanding of microbial populations. Biotechnology Journal, 9(1): 61-72.

31. Lencastre Fernandes, R., Nierychlo, M., Lundin, L., Pedersen, A.E., Puentes Tellez, P.E., Dutta, A., et al. (2011) Experimental methods and modeling techniques for description of cell population heterogeneity. Biotechnology Advances, 29(6): 575-599.
32. Delvigne, F., Boxus, M., Ingels, S., Thonart, P. (2009) Bioreactor mixing efficiency modulates the activity of a prpoP:GFP reporter gene in recombinant Escherichia coli. Microbial Cell Factories, 8: 15.
33. Sweere, A.P.J., Luyben, K.C.A.M., Kossen, N.W.F. (1987) Regime analysis and scale-down: tools to investigate the performance of bioreactors. Enzyme and Microbial Technology, 9(7): 386-398.
34. Neubauer, P., Junne, S. (2010) Scale-down simulators for metabolic analysis of large-scale bioprocesses. Current Opinion in Biotechnology, 21(1): 114-121.
35. Gernaey, K.V., Lantz, A.E., Tufvesson, P., Woodley, J.M., Sin, G. (2010) Application of mechanistic models to fermentation and biocatalysis for next-generation processes. Trends in Biotechnology, 28(7): 346-354.